

AMAXX® receptacle combination

Part no. 920024



- pre-wired for installation
- hinged to the side


•

enclosure and insert made of AMAPLAST

Technical specifications

CEE 16 A, 5 p, 400 V	2
SCHUKO® 16 A, 230 V	2
Connection / feeder cable	 for 1 cable up to 5 x 10 mm² and 1 cable up to 3 x 10 mm²
Protection type	IP 44
Shutter	false
Enclosure material	Plastic
Weight	2680 g
Height	260 mm
Width	225 mm
Declaration of Conformity	EAC

Drawing



Drawing 1 MB 521

Depth dimensions at vario	us fittings.		
Receptacles	Degrees	Depth	
SCHUKO [®] 16A, 230 V	IP 44	175 mm	
	IP 67	194 mm	
CEE 16A, 3p, 230V	IP 44	204 mm	
	IP 67	205 mm	
CEE 16A, 5p, 400V	IP 44	209 mm	
	IP 67	213 mm	
CEE 32A, 5p, 400V	IP 44	221 mm	
	IP 67	227 mm	
CEE 63A, 5p, 400V	IP 44	248 mm	
	IP 67	248 mm	
Cable entries: closed for cut out 2 x M 22 each on ten and bettern			

Cable entries: closed for cut out, 2 x M 32 each on top and bottom, 2 x M 20 each on top and bottom for cut out.